

WHAT IS CLAIMED IS:

1. A vehicular parking brake apparatus, comprising:
 - a right-side parking brake and a left-side parking brake that brake a right-side wheel and a left-side wheel, respectively, of at least one group of a front wheel group and a rear wheel group of a vehicle;
 - a drive power source that operates the right-side parking brake and the left-side parking brake; and
 - a controller that controls the drive power source, the controller including an antilock control portion that commonly controls an operating force of the right-side parking brake and an operating force of the left-side parking brake produced by driving the drive power source, based on a state of slip of a wheel of the right-side wheel and the left-side wheel that exhibits a greater change in a state of wheel rotation.
2. The vehicular parking brake apparatus according to claim 1, wherein the drive power source commonly drives the right-side parking brake and the left-side parking brake, and the right-side parking brake and the left-side parking brake comprise:
 - brakes that are provided for the right-side wheel and the left-side wheel, respectively; and
 - a transfer device that connects the brakes to the drive power source and has an equalizer which distributes a drive power of the drive power source equally to the brake of the right-side wheel and the brake of the left-side wheel.
3. The vehicular parking brake apparatus according to claim 2, wherein the antilock control portion comprises a common drive power source control portion that commonly controls the operating force of the right-side parking brake and the operating force of the left-side parking brake by controlling the common drive power source.
4. The vehicular parking brake apparatus according to claim 3, wherein the antilock control portion commonly controls the operating force of the right-side parking brake and the operating force of the left-side parking brake based on the state of slip of the wheel of the right-side wheel and the left-side wheel that exhibits a greater slip.

0927386-081301

10. The vehicular parking brake apparatus according to claim 9, wherein the parking brake controller has a hold state in which the drive power source is operated so that the operating force of the parking brake is maintained, and the parking brake controller sets the hold state at a time of switching between the increase state and the decrease state.

11. The vehicular parking brake apparatus according to claim 10, wherein the parking brake controller sets the drive power source to the decrease state if the state of slip of the wheel exceeds a predetermined upper threshold.

12. The vehicular parking brake apparatus according to claim 11, wherein the parking brake controller sets the drive power source to the increase state at a time point when the state of slip of the wheel starts to decrease from a peak value.

13. The vehicular parking brake apparatus according to claim 10, wherein the parking brake controller sets the drive power source to the increase state at a time point when the state of slip of the wheel starts to decrease from a peak value.

14. The vehicular parking brake apparatus according to claim 9, wherein the parking brake controller sets the drive power source to the decrease state if the state of slip of the wheel exceeds a predetermined upper threshold.

15. The vehicular parking brake apparatus according to claim 14, wherein the parking brake controller sets the drive power source to the increase state at a time point when the state of slip of the wheel starts to decrease from a peak value.

16. The vehicular parking brake apparatus according to claim 9, wherein the parking brake controller sets the drive power source to the increase state at a time point when the state of slip of the wheel starts to decrease from a peak value.

17. A control method of a vehicular parking brake apparatus, comprising:
determining a change in a state of rotation of one of a right-side wheel and a left-side wheel;

determining a state of slip of one of the right-side wheel and the left-side wheel that exhibits a greater change in the state of rotation; and

commonly controlling an operating force of a right-side parking brake and an operating force of a left-side parking brake based on the determined state of slip.

18. A control method of a vehicular parking brake apparatus, comprising:

00027355.001301

increasing/decreasing a drive power of a drive power source that operates the parking brake while reducing an overshoot of the state of slip; and controlling the operating force of the parking brake by increasing/decreasing the drive power.

10 operating a drive power source that operates the parking brake, to
increase an operating force of the parking brake, based on the state of slip;
 operating the drive power source to decrease the operating force of the
parking brake if the state of slip exceeds a predetermined upper threshold; and
 operating the drive power source to increase the operating force of the
15 parking brake at a time point when the state of slip of the wheel starts to decrease
from a peak value.

20. The control method according to claim 19, wherein the drive power source is operated to keep the operating force of the parking brake at a constant value when the operating force of the parking brake is increased and then decreased, and
20 when the operating force of the parking brake is decreased and then increased.